

(1) **Certificate of Conformity**

(2) Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres – **Directive 2014/34/EU**

(3) Certificate Number:

EPS 19 ATEX 1 074 X

Revision 0

(4) Equipment: IS330.2 Intrinsically safe multifunctional Feature phone

(5) Manufacturer: i.safe MOBILE GmbH

(6) Address: i_Park Tauberfranken 10
97922 Lauda-Koenigshofen
Germany

(7) This equipment and any acceptable variation thereto are specified in the schedule to this Certificate of Conformity and the documents therein referred to.

(8) Bureau Veritas Consumer Products Services Germany GmbH certifies based on a voluntary assessment that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres, given in Annex II of the Directive 2014/34/EU. The examination and test results are recorded in the confidential documentation under the reference number 19TH0204.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN IEC 60079-0:2018

EN 60079-11:2012

(10) If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.

(11) This Certificate of Conformity relates only to the design and the construction of the specified equipment in accordance with Directive 2014/34/EU. Further requirements of this Directive apply to the manufacture and supply of this equipment. Those requirements are not covered by this certificate.

(12) The marking of the equipment shall include the following:



II 3G Ex ic IIC T4 Gc IP64

II 3D Ex ic IIIC T135°C Dc IP64

Certification department of explosion protection

Hamburg, 2020-05-04

H. Schaffer



(13)

Annex

(14) **Certificate of Conformity EPS 19 ATEX 1 074 X**

Revision 0

(15) Description of equipment:

The IS330.2 is the intrinsically safe, multifunctional Feature phone for the rugged use in explosion hazardous areas of zone 2 and 22. It has a PTT and SOS button and an ISM interface for intrinsically safe and approved headsets, remote speaker microphones and add-ons, making the Feature phone a universal tool for any application. The IS330.2 is equipped with an Android operating system, efficient processor, amplified loudspeaker and a replaceable battery. Technologies like 4G (LTE), NFC, GPS, Bluetooth and Wi-Fi complete the performance.

Electrical data:

Supply:

The Feature phone IS330.2 has a replaceable Li-Ion battery $U_0 = 3.8 \text{ V}$ ($U_{0_max} = 4.2 \text{ V}$).

Interfaces:

The device has two charging contacts ($U_m = 5.88 \text{ V}$), with which it can be charged outside hazardous areas via an approved charging adapter. The contacts are intrinsically safe for gas and dust.

Furthermore, the device has an USB interface type C ($U_m = 5.88 \text{ V}$) for charging and data transmission outside hazardous areas. It is not permitted to open the USB interface cover in hazardous areas.

The ISM interface of the IS330.2 can be used within hazardous areas with approved headsets, Remote Speaker Microphones (RSM) and add-ons, making the Feature phone a multifunctional equipment for industrial applications. For ISM interface use, the i.safe MOBILE headset IS-HS1.1, IS-HS1.2 or i.safe MOBILE approved, intrinsically safe accessories may be used, which comply with the connection parameters of the ISM interface according to document 1029AD04. If the ISM interface is not used, it must be securely closed by the cover provided for this purpose.

A commercially available SD card may be used in the corresponding slot in the hazardous area. The internal electrical capacity of the SD card is negligible.

(16) Reference number: 19TH0204

(17) Schedule of Limitations:

The battery may be charged and replaced outside explosion hazardous areas only.

The device must be protected from impacts with high impact energy, against excessive UV light emission and high electrostatic charge processes.

The permitted ambient temperature range is $-20 \text{ }^\circ\text{C}$ to $+60 \text{ }^\circ\text{C}$.

(18) Essential health and safety requirements:

Met by standards.

Certification department of explosion protection

Hamburg, 2020-05-04

H. Schaffer

